

## Female to Female 6 x MPO Trunk Cable Assembly 72 Fibers OM3 OFNR Aqua Jack

Our Product Introduction

for more products please visit us on [optical-fibercables.com](http://optical-fibercables.com)

### Basic Information

- Place of Origin: Shenzhen, China
- Brand Name: FiberMania
- Certification: ISO, UL, CE, RoHS
- Model Number: MPFLC-M38M3RAQ
- Minimum Order Quantity: 10 Pieces
- Price: Negotiable
- Packaging Details: PE bag or OEM service optional
- Delivery Time: 5 days
- Payment Terms: T/T, Western Union, L/C
- Supply Ability: 10000 Pieces per day



### Product Specification

- Connector Type: MPO Female
- Fiber Count: 72 Fibers
- Polarity: Type A
- Cable (OD): 3.0mm
- Fiber Mode: OM3 50/125μm
- Wavelength: 850/1300nm
- Cable Jacket: OFNR
- Jacket Color: Aqua
- Name: MPO Solutions
- Highlight: **6 x MPO Trunk Cable, Female to Female MPO Trunk Cable**



### More Images



## Product Description

### 6 x MPO Female to 6 x MPO Female Trunk Cable Assembly 72 Fibers OM3 OFNR Aqua Jack

The MPO trunk cables with a braided tubing jacket are typically designed for a longer cable length in cabinet-to-cabinet applications or for connecting different areas of a building. MPO cable, a cost-effective alternative to time-consuming field termination, is designed for high-density fiber patching in data centers which need space saving and reduce cable management problems.

#### Applications of MPO Trunk Patch Cable

1. Datacenter
2. Telecommunication networks
3. High-density cross-connects
4. Optical switch inter-frame connection

#### Features of MPO MPO Trunk Patch Cable

1. Various fiber counts are available
2. Good exchangeability
3. Plug and Play Ready
4. Standard: Telcordia GR-1435-CORE compliant

#### Specifications of MPO Trunk Patch Cable

Connector	MPO(Female)
Fiber Mode	OM3 50/125μm
Polishing Type	UPC
Connector IL	0.35dB Max (0.15dB Typ.)
Connector RL	≥20dB
Breakout Type	0.3m Equal Breakout
Glass Fiber	Corning ClearCurve®
10G Ethernet Distance	400m at 850nm
Attenuation at 850nm	≤2.3dB/km
Attenuation at 1300nm	≤0.6dB/km
Installation Tensile Load	66N
Tensile Strength (Long/Short Term)	80/240N
Storage Temperature	-40 to +85°C
Operating Temperature	-20 to +85°C



**FIBERMANIA** Shenzhen FiberMania Technology Co., Ltd.



17704025189



[sales@fiber-mania.com](mailto:sales@fiber-mania.com)



[optical-fibercables.com](http://optical-fibercables.com)

3F, Building A2, Yinlong Industrial Park, Longdong, Longgang District, Shenzhen, China, 518116