

FTTA FullAXS to LC UPC Patch Cord 2 Cores 9/125 OS2 TPU Jacket

Our Product Introduction

for more products please visit us on optical-fibercables.com

Basic Information

- Place of Origin: Shenzhen, China
- Brand Name: FIBERMANIA
- Certification: RoHS, CE, ISO9001, VDE, CCC
- Model Number: FXLC-SM025TBK
- Minimum Order Quantity: 10 Pieces
- Price: Negotiable
- Packaging Details: PE bag or OEM service optional
- Payment Terms: T/T, Western Union, L/C
- Supply Ability: 1000 Pieces



Product Specification

- Connector Type: FullAXS To LC
- Polish Type: UPC To UPC
- Fiber Grade: Corning G.657.A1
- Fiber Count: Duplex
- Cable (OD): 5.0mm
- Cable Jacket: TPU
- Jacket Color: Black
- Application: Outdoor Or FTTA
- Name: FTTA Solutions
- Highlight: **FTTA FullAXS to LC UPC Patch Cord , OS2 Patch Cord**



More Images



Product Description

FTTA FullAXS to LC UPC Patch Cord 2 Cores 9/125 OS2 TPU Jacket

FiberMania's FTTA (Fiber To The Antenna) FullAXS patch cord is designed to accommodate for a large tolerance in Z-direction and offer the benefit of one-hand installation of the connector shell. With this new product offering, users can also conveniently remove and replace transceivers through a cutout in the bulkhead that completely eliminates the need to open the entire remote radio box and expose its contents to hazardous weather conditions. For the optical connection, the connector system includes an industry-standard duplex LC interface for fast mating with all LC duplex SFP transceivers.

Features

1. Fiber Cable: OS2 Single Mode GYFJH, 4.8mm, 2 Cores, TPU Jacket, Black
2. Positive mechanical feedback to the operator when fully mated
3. Available for single and multimode
4. Waterproof, dustproof and corrosion-resistant
5. Tensile data: Between junction and fiber cable $\geq 180N$
6. Outer shell inflaming retarding: UL 94V-0
7. RoHS compliant

Application

1. WiMAX and LTE Base Stations
2. Remote radio heads (RRH)
3. Industrial outdoor applications
4. Aerospace & Defense

Fiber Parameters

No.	Items	Unit	Value	
1	Core Diameter	um	9/125: G652D, G657A1, G657A2 62.5/125: OM1: 62.5 50/125: OM2, OM3, OM4, OM5	
2	Cladding Diameter	um	125±10	
3	Core Non-Circularity	%	≤6.0	
4	Cladding Non-Circularity	%	≤2.0	
5	Core-Cladding Concentricity	um	≤1.0	
6	Coating Diameter	um	245±10	
7	Cladding-Coating Concentricity	um	≤12.5	
8	Attenuation (Max.)	850nm	dB/km	3.0
		1300nm	dB/km	1.0
		1310nm	dB/km	0.35
		1550nm	dB/km	0.22

Cable Parameters

Items		Value
Fiber Count		2 or 4
Buffer	Diameter	0.85mm \pm 0.05mm
	Material	LSZH
Simpelx Cable	Diameter	2.0mm \pm 0.1mm
	Material	LSZH
Filler	Diameter	2.0mm \pm 0.1mm
	Material	LSZH
Strength Member		Kevlar
Jacket	Material	LSZH
	Color	Black
Cable Weight	Approx.	47kg/km

Characteristics Mechanical and Environmental

Items	Unite	Value
Tensile (Long Term)	N	200
Tensile (Short Term)	N	400
Crush(Long Term)	N/10cm	1100
Crush (Short Term)	N/10cm	2200
Bend Radius (Dynamic)	mm	20D
Bend Radius (Static)	mm	10D
Installation temperature	°C	-20~+60
Operation temperature	°C	-30~+70
Storage temperature	°C	-30~+70

Specification

End face type	UPC
Fiber type	G657A1
Cable Diameter	4.8mm
Insertion loss	≤ 0.3 dB
Return loss	≥ 50 dB
Attenuation at 1310nm	0.36 dB/km
Attenuation at 1550nm	0.22 dB/km
Tensile Strength	200/400N (Long/Short Term)
Crush Resistance	1100/2200N (Long/Short Term)
Working Temperature	-40 ~ +70°C
Storage Temperature	-40 ~ +70°C
Operating Temperature	-10 ~ +50°C

Length	Customized
--------	------------



FAQ

Q1: What is the warranty of FiberMania's fiber patch cord?

A: FiberMania warrants that all fiber patch cords supplied are free from defects in material and workmanship for a period of five (5) years from the date of supply. All fiber optic bulk cables are UL profiled and every single cable is 100% tested.

Q2: Is it possible to customize our brand information on your fiber cable?

A: Yes, we can print your brand name onto our cable jacket and 1KM total cable length is requested.

Q3: Can you do 3D interferometer test?

A: Yes, we do the 3D test per our customer's request, we can have the pass rate over 90% and even 100% if necessary.

Q4: What is your MOQ of your products?

A: We only have MOQ for some special customized cable order, we request 1km as the total length of the bulk cable, you may consider stock the bulk cable with us for your urgent order production.

Q5: Are free samples available from you?

A: Yes, we are always happy to offer the free samples for all of our customers' projects provided that the total cost is under 50 US dollars.

Q6: Do you accept OEM and ODM orders?

A: Absolutely yes, we have been doing OEM services since we start in this business, and for every single label, printing, bag and carton design, we always treat it seriously and do it nicely. Our engineers can help you with your current design and even can open the new tooling for your

specific project.



FIBERMANIA **Shenzhen FiberMania Technology Co., Ltd.**



17704025189



sales@fiber-mania.com



optical-fibercables.com

3F, Building A2, Yinlong Industrial Park, Longdong, Longgang District, Shenzhen, China, 518116