

FullAXS To ODC Socket FTTA Patch Cord 2 Cores 9/125 OS2 TPU Jacket

Our Product Introduction

for more products please visit us on optical-fibercables.com

Basic Information

- Place of Origin: Shenzhen, China
- Brand Name: FIBERMANIA
- Certification: RoHS, CE, ISO9001, VDE, CCC
- Model Number: FXOS-SM024TBK
- Minimum Order Quantity: 10 Pieces
- Price: Negotiable
- Packaging Details: PE bag or OEM service optional
- Payment Terms: T/T, Western Union, L/C
- Supply Ability: 1000 Pieces



Product Specification

- Connector Type: FullAXS To ODC
- Polish Type: UPC To UPC
- Fiber Grade: Corning G.657.A1
- Fiber Count: Duplex
- Cable (OD): 4.8mm
- Cable Jacket: TPU
- Jacket Color: Black
- Application: Outdoor Or FTTA
- Name: FTTA Solutions
- Highlight: **FullAXS to ODC FTTA Patch Cord, UPC to UPC FTTA Patch Cord, FullAXS patch cord**



More Images



Product Description

FTTA FullAXS to ODC Socket Patch Cord 2 Cores 9/125 OS2 TPU Jacket

FullAXS To ODC Socket FTTA Patch Cord 2 Cores 9/125 OS2 TPU Jacket is an outdoor fiber optic patch cord specially designed for fiber to tower (FTTA) applications. It uses a FullAXS connector on one end, which is a waterproof and dustproof connector that meets IP67 standards, and with an ODC socket on the other end, which is an outdoor fiber optic connector designed for fast and reliable connection directly on the fiber optic cable. Both connectors are very suitable for harsh outdoor environments. At the same time, this patch cable is covered with a thermoplastic polyurethane (TPU) sheath, providing additional wear resistance and protection. This type of jumper is suitable for outdoor fiber optic transmission, such as in applications such as Cable TV networks, LAN testing/measuring instruments, FTTA, FTTP, FTTX, WIMAX, etc.

Features

1. Fiber Cable: OS2 Single Mode GYFJH, 4.8mm, 2 Cores, TPU Jacket, Black
2. Positive mechanical feedback to the operator when fully mated
3. Available for single and multimode
4. Waterproof, dustproof and corrosion-resistant
5. Tensile data: Between junction and fiber cable $\geq 180\text{N}$
6. Outer shell inflaming retarding: UL 94V-0
7. RoHS compliant

Application

1. WiMAX and LTE Base Stations
2. Remote radio heads (RRH)
3. Industrial outdoor applications
4. Aerospace & Defense

Fiber Parameters

Fiber Parameters				
No.	Items		Unit	Value
1	Core Diameter		um	9/125: G652D, G657A1, G657A2 62.5/125: OM1: 62.5 50/125: OM2, OM3, OM4, OM5
2	Cladding Diameter		um	125±10
3	Core Non-Circularity		%	≤6.0
4	Cladding Non-Circularity		%	≤2.0
5	Core-Cladding Concentricity		um	≤1.0
6	Coating Diameter		um	245±10
7	Cladding-Coating Concentricity		um	≤12.5
8	Attenuation (Max.)	850nm	dB/km	3.0
		1300nm	dB/km	1.0
		1310nm	dB/km	0.35
		1550nm	dB/km	0.22

Cable Parameters

Items		Value
Fiber Count		2 or 4
Buffer	Diameter	0.85mm \pm 0.05mm
	Material	LSZH
Simpelx Cable	Diameter	2.0mm \pm 0.1mm
	Material	LSZH
Filler	Diameter	2.0mm \pm 0.1mm
	Material	LSZH
Strength Member		Kevlar
Jacket	Material	LSZH
	Color	Black
Cable Weight	Approx.	47kg/km

Characteristics Mechanical and Environmental

Items	Unit	Value
Tensile (Long Term)	N	200
Tensile (Short Term)	N	400
Crush(Long Term)	N/10cm	1100
Crush (Short Term)	N/10cm	2200
Bend Radius (Dynamic)	mm	20D
Bend Radius (Static)	mm	10D
Installation temperature	°C	-20~+60
Operation temperature	°C	-30~+70
Storage temperature	°C	-30~+70

Specification

End face type	UPC
Fiber type	G657A1
Cable Diameter	4.8mm
Insertion loss	≤ 0.3 dB
Return loss	≥ 50 dB
Attenuation at 1310nm	0.36 dB/km
Attenuation at 1550nm	0.22 dB/km
Tensile Strength	200/400N (Long/Short Term)
Crush Resistance	1100/2200N (Long/Short Term)
Working Temperature	-40 ~ +70°C
Storage Temperature	-40 ~ +70°C

Operating Temperature	-10 ~ +50°C
Length	Customized



FAQ

Q1: What is the warranty of FiberMania's fiber patch cord?

A: FiberMania warrants that all fiber patch cords supplied are free from defects in material and workmanship for a period of five (5) years from the date of supply. All fiber optic bulk cables are UL profiled and every single cable is 100% tested.

Q2: Is it possible to customize our brand information on your fiber cable?

A: Yes, we can print your brand name onto our cable jacket and 1KM total cable length is requested.

Q3: Can you do 3D interferometer test?

A: Yes, we do the 3D test per our customer's request, we can have the pass rate over 90% and even 100% if necessary.

Q4: What is your MOQ of your products?

A: We only have MOQ for some special customized cable order, we request 1km as the total length of the bulk cable, you may consider stock the bulk cable with us for your urgent order production.

Q5: Are free samples available from you?

A: Yes, we are always happy to offer the free samples for all of our customers' projects provided that the total cost is under 50 US dollars.

Q6: Do you accept OEM and ODM orders?

A: Absolutely yes, we have been doing OEM services since we start in this business, and for every single label, printing, bag and carton design, we always treat it seriously and do it nicely. Our engineers can help you with your current design and even can open the new tooling for your specific project.



FIBERMANIA Shenzhen FiberMania Technology Co., Ltd.



17704025189



sales@fiber-mania.com



optical-fibercables.com

3F, Building A2, Yinlong Industrial Park, Longdong, Longgang District, Shenzhen, China, 518116