

FTTA OptiTap MPO To 12xLC UPC Duplex Fiber Patch Cable 9/125 G.657.A1 LSZH Jacket

Our Product Introduction

for more products please visit us on optical-fibercables.com


Basic Information

- Place of Origin: Shenzhen, China
- Brand Name: FIBERMANIA
- Certification: RoHS, CE, ISO9001, VDE, CCC
- Model Number: OTMPLC-SM244LBK
- Minimum Order Quantity: 10 Pieces
- Price: Negotiable
- Packaging Details: PE bag or OEM service optional
- Payment Terms: T/T, Western Union, L/C
- Supply Ability: 1000 Pieces



Product Specification

- Name: Duplex Fiber Patch Cable
- Connector Type: OptiTap MPO To LC
- Polish Type: UPC To UPC
- Fiber Grade: G657A1
- Fiber Count: 24 Cores
- Cable (OD): 4.8mm
- Cable Jacket: LSZH
- Jacket Color: Black
- Application: Outdoor Or FTTA
- Highlight: **OptiTap to LC Duplex Fiber Patch Cable,
FTTA Duplex Fiber Patch Cable,
CCC Duplex Fiber Patch Cable**



More Images



Product Description

FTTA OptiTap MPO to 12xLC UPC Duplex Outdoor Waterproof Cable 9/125 G.657.A1 LSZH Jacket


FTTA OptiTap MPO to 12xLC UPC Duplex Outdoor Waterproof Cable is a fiber optic cable used in communication networks, mainly for transmitting optical signals from base stations to antennas. This waterproof cable uses MPO waterproof connectors on one end and 12 LC duplex connectors on the other end, which can simultaneously transmit multiple optical signals. This cable is designed for outdoor use and has waterproof characteristics, which can be used in various weather conditions to ensure stable signal transmission. It is suitable for various application scenarios such as FTTA projects, outdoor communication, oil and gas industry, marine and submarine communication, industrial automation, and mining operations.

Features

1. Fiber Cable: OS2 Single Mode GYFJH, 4.8mm, 24Cores, LSZH Jacket, Black
2. Positive mechanical feedback to the operator when fully mated
3. Robust bayonet locking for easy, fast, and secure mating
4. Available for single mode and multimode
5. Waterproof, dustproof and corrosion-resistant
6. Protection level: IP67
7. Tensile data: Between junction and fiber cable $\geq 180\text{N}$
8. Outer shell inflaming retarding: UL 94V-0
9. RoHS compliant

Application

1. Indoor and Outdoor applications
2. FTTA applications
3. Oil and gas industry
4. Ocean and submarine communications
5. Optical fiber sensor
6. Industrial automation
7. Mining operation



Fiber Parameters

No.	Items	Unit	Value
1	Core Diameter	um	9/125: G652D, G657A1, G657A2 62.5/125: OM1: 62.5 50/125: OM2, OM3, OM4, OM5
2	Cladding Diameter	um	125 \pm 10
3	Core Non-Circularity	%	≤ 6.0
4	Cladding Non-Circularity	%	≤ 2.0
5	Core-Cladding Concentricity	um	≤ 1.0
6	Coating Diameter	um	245 \pm 10
7	Cladding-Coating Concentricity	um	≤ 12.5
8	Attenuation (Max.)	850nm	dB/km
		1300nm	dB/km
		1310nm	dB/km
		1550nm	dB/km

Cable Parameters

Items		Value
Fiber Count		2 or 4
Buffer	Diameter	0.85mm \pm 0.05mm
	Material	LSZH
Simplex Cable	Diameter	2.0mm \pm 0.1mm
	Material	LSZH
Filler	Diameter	2.0mm \pm 0.1mm
	Material	LSZH
Strength Member		Kevlar
Jacket	Material	LSZH
	Color	Black
Cable Weight	Approx.	47kg/km

Characteristics Mechanical and Environmental

Items	Unite	Value
-------	-------	-------

Tensile (Long Term)	N	200
Tensile (Short Term)	N	400
Crush(Long Term)	N/10cm	1100
Crush (Short Term)	N/10cm	2200
Bend Radius (Dynamic)	mm	20D
Bend Radius (Static)	mm	10D
Installation temperature	°C	-20~+60
Operation temperature	°C	-30~+70
Storage temperature	°C	-30~+70

Specification

End face type	UPC
Fiber type	G657A1
Cable Diameter	5.0mm
Insertion loss	≤ 0.3 dB
Return loss	≥50dB
Attenuation at 1310nm	0.36 dB/km
Attenuation at 1550nm	0.22 dB/km
Tensile Strength	200/400N (Long/Short Term)
Crush Resistance	1100/2200N (Long/Short Term)
Working Temperature	-40 ~ +70°C
Storage Temperature	-40 ~ +70°C
Operating Temperature	-10 ~ +50°C
Length	Customized





FAQ

Q1: What is the warranty of FiberMania's fiber patch cord?

A: FiberMania warrants that all fiber patch cords supplied are free from defects in material and workmanship for a period of five (5) years from the date of supply. All fiber optic bulk cables are UL profiled and every single cable is 100% tested.

Q2: Is it possible to customize our brand information on your fiber cable?

A: Yes, we can print your brand name onto our cable jacket and 1KM total cable length is requested.

Q3: Can you do 3D interferometer test?

A: Yes, we do the 3D test per our customer's request, we can have the pass rate over 90% and even 100% if necessary.

Q4: What is your MOQ of your products?

A: We only have MOQ for some special customized cable order, we request 1km as the total length of the bulk cable, you may consider stock the bulk cable with us for your urgent order production.

Q5: Are free samples available from you?

A: Yes, we are always happy to offer the free samples for all of our customers' projects provided that the total cost is under 50 US dollars.

Q6: Do you accept OEM and ODM orders?

A: Absolutely yes, we have been doing OEM services since we start in this business, and for every single label, printing, bag and carton design, we always treat it seriously and do it nicely. Our engineers can help you with your current design and even can open the new tooling for your specific project.



FIBERMANIA Shenzhen FiberMania Technology Co., Ltd.



17704025189



sales@fiber-mania.com



optical-fibercables.com

3F, Building A2, Yinlong Industrial Park, Longdong, Longgang District, Shenzhen, China, 518116