


## LC UPC To LC UPC Fiber Optic Adapters Duplex Single Mode Fiber Coupler

Our Product Introduction

for more products please visit us on [optical-fibercables.com](http://optical-fibercables.com)


### Basic Information

- Place of Origin: Shenzhen, China
- Brand Name: FIBERMANIA
- Certification: ISO, UL, CE, RoHS
- Model Number: LCLCSDC
- Minimum Order Quantity: 10 Pieces
- Price: Negotiable
- Packaging Details: Plastic Container + Carton
- Delivery Time: 7-10 working days
- Payment Terms: T/T, Western Union, L/C
- Supply Ability: 100000PCS/Month




### Product Specification

- Body Style: Duplex
- Polish Type: UPC
- Name: Fiber Optic Adapters
- Connector Type: LC To LC
- Color: Blue
- Fiber Mode: OS2 9/125μm
- Insertion Loss: ≤0.2dB
- Durability: 500 Times
- Flammability Rate: UL 94V-0
- Highlight: **LC UPC To LC UPC Fiber Optic Adapters , Fiber Optic Adapters Duplex, Single Mode Fiber Coupler LC To LC**



### More Images



## Product Description

### LC UPC To LC UPC Single Mode Duplex Plastic Fiber Optic Adapter/Coupler – Blue

The LC duplex single-mode fiber optic adapter is a specialized device designed for duplex single-mode fiber connections, featuring a compact and high-density design. It facilitates low insertion loss and high return loss, ensuring optimal signal quality during long-distance transmission. This adapter is widely utilized in data centers, fiber optic communication networks, and telecommunications infrastructure, making it especially suitable for environments that demand high bandwidth and exceptional performance. As a key component of modern fiber optic connections, it plays a vital role in enhancing both network efficiency and reliability.

#### Features

1. Low insertion loss
2. High corrosion resistance
3. High interface performance
4. High return loss
5. Easy to handle
6. Environmentally stable

#### Application

1. Data center
2. Telecommunication networks
3. Premise installations
4. LAN and WAN
5. FTTX
6. Broadband network

#### Mechanical Specifications

Operating Temperature	-40 to +75° C
Storage Temperature	-40 to +85° C
Temperature Cycling	-40 to +75° C, 40 cycles=0.2dB change
High Temperature	70 °c for 96Hrs, <0.4dB change
Damp Heat	40° C at 93%RH for 96 Hrs, <0.4dB change
Vibration-Mated Pair	10-55Hz, 1.5mm P to P <0.2dB change
Mating Durability	500 Mating Cycles, clean every 25, <0.2dB change





#### FAQ

Q1: What is the warranty of FiberMania's fiber patch cord?

A: FiberMania warrants that all fiber patch cords supplied are free from defects in material and workmanship for a period of five (5) years from the date of supply. All fiber optic bulk cables are UL profiled and every single cable is 100% tested.

Q2: Is it possible to customize our brand information on your fiber cable?

A: Yes, we can print your brand name onto our cable jacket and 1KM total cable length is requested.

Q3: Can you do 3D interferometer test?

A: Yes, we do the 3D test per our customer's request, we can have the pass rate over 90% and even 100% if necessary.

Q4: What is your MOQ of your products?

A: We only have MOQ for some special customized cable order, we request 1km as the total length of the bulk cable, you may consider stock the bulk cable with us for your urgent order production.

Q5: Are free samples available from you?

A: Yes, we are always happy to offer the free samples for all of our customers' projects provided that the total cost is under 50 US dollars.

Q6: Do you accept OEM and ODM orders?

A: Absolutely yes, we have been doing OEM services since we start in this business, and for every single label, printing, bag and carton design, we always treat it seriously and do it nicely. Our engineers can help you with your current design and even can open the new tooling for your specific project.



**FIBERMANIA** Shenzhen FiberMania Technology Co., Ltd.



17704025189



[sales@fiber-mania.com](mailto:sales@fiber-mania.com)



[optical-fibercables.com](http://optical-fibercables.com)

3F, Building A2, Yinlong Industrial Park, Longdong, Longgang District, Shenzhen, China, 518116