

ST Female to SC Male Single Mode Simplex Fiber Optic Adapter/Coupler without Flange

Our Product Introduction

for more products please visit us on optical-fibercables.com

Basic Information

- Place of Origin: Shenzhen, China
- Brand Name: FIBERMANIA
- Certification: ISO, UL, CE, RoHS
- Model Number: SCMSTFSS
- Minimum Order Quantity: 10 Pieces
- Price: Negotiable
- Packaging Details: Plastic Container + Carton
- Delivery Time: 7-10 working days
- Payment Terms: T/T, Western Union, L/C
- Supply Ability: 100000PCS/Month



Product Specification

- Connector Type: SC Female To ST Male
- Body Style: Simplex
- Durability: 1000 Times
- Polish Type: UPC
- Fiber Mode: OS2 9/125μm
- Insertion Loss: ≤0.2dB
- Anti Pulling Force: 200-600G
- Flammability Rate: UL 94V-0
- Highlight: SC Male Fiber Optic Adapter



More Images



Product Description

ST Female to SC Male Single Mode Simplex Fiber Optic Adapter/Coupler without Flange

The SC to ST single-mode fiber optic adapter is a specialized device designed to connect SC and ST type fiber connectors, specifically engineered for single-mode fiber applications. It offers high-precision mating performance, enabling low insertion loss and high return loss to ensure stable, high-quality signal transmission over long distances. This adapter is widely utilized in telecommunications networks, data centers, and fiber optic communication systems, making it ideal for environments that demand high bandwidth and exceptional performance. As an essential component of modern fiber optic connections, it plays a vital role in enhancing network reliability and efficiency.

Features

1. Meet IEC, Telcordia-GR-326 and JIS performance requirement.
2. High precision alignment sleeve
3. Materials compliant to RoHS
4. 100% inspected prior to shipment

Application

1. Data center
2. Telecommunication networks
3. Premise installations
4. LAN and WAN
5. FTTX
6. Broadband network

Mechanical Specifications

Operating Temperature	-40 to +75° C
Storage Temperature	-40 to +85° C
Temperature Cycling	-40 to +75° C, 40 cycles=0.2dB change
High Temperature	70°c for 96Hrs, <0.4dB change
Damp Heat	40° C at 93%RH for 96 Hrs, <0.4dB change
Vibration-Mated Pair	10-55Hz, 1.5mm P to P <0.2dB change
Mating Durability	500 Mating Cycles, clean every 25, <0.2dB change





FAQ

Q1: What is the warranty of FiberMania's fiber patch cord?

A: FiberMania warrants that all fiber patch cords supplied are free from defects in material and workmanship for a period of five (5) years from the date of supply. All fiber optic bulk cables are UL profiled and every single cable is 100% tested.

Q2: Is it possible to customize our brand information on your fiber cable?

A: Yes, we can print your brand name onto our cable jacket and 1KM total cable length is requested.

Q3: Can you do 3D interferometer test?

A: Yes, we do the 3D test per our customer's request, we can have the pass rate over 90% and even 100% if necessary.

Q4: What is your MOQ of your products?

A: We only have MOQ for some special customized cable order, we request 1km as the total length of the bulk cable, you may consider stock the bulk cable with us for your urgent order production.

Q5: Are free samples available from you?

A: Yes, we are always happy to offer the free samples for all of our customers' projects provided that the total cost is under 50 US dollars.

Q6: Do you accept OEM and ODM orders?

A: Absolutely yes, we have been doing OEM services since we start in this business, and for every single label, printing, bag and carton design, we always treat it seriously and do it nicely. Our engineers can help you with your current design and even can open the new tooling for your specific project.



FIBERMANIA Shenzhen FiberMania Technology Co., Ltd.



17704025189



sales@fiber-mania.com



optical-fibercables.com

3F, Building A2, Yinlong Industrial Park, Longdong, Longgang District, Shenzhen, China, 518116