

SC Female to ST Female Multimode Duplex Plastic Fiber Optic Adapter -Beige

Basic Information

. Place of Origin: Shenzhen, China . Brand Name: **FIBERMANIA** ISO, UL, CE, RoHS · Certification: SCMSTF1S Model Number: • Minimum Order Quantity: 10 Pieces • Price:

· Packaging Details: Plastic Container + Carton • Delivery Time: 7-10 working days Payment Terms: T/T, Western Union, L/C 100000PCS/Month . Supply Ability:

Negotiable



Product Specification

. Connector Type: SC Female To ST Female

· ApplicationRate: Fiber Distribution Frame, Network

Equipment, Fiber Module

UPC Polish Type: . Body Style: Duplex ≤0.2dB Insertion Loss: Multimode • Fiber Mode: 200-600G Anti Pulling Force: • Durability: 1000 Times

Highlight: Beige Fiber Optic Adapter,

Plastic Fiber Optic Adapter



More Images



Product Description

SC Female to ST Female Multimode Duplex Plastic Fiber Optic Adapter - Beige

FiberMania's line of simplex and duplex APC couplers feature tightly tolerance slots to assure proper orientation of mated APC connectors. In order to achieve low back reflection values some fiber assemblies utilize a connector with an Angled Polish Contact (APC). Our couplers feature a ceramic sleeves to ensure precise alignment and signal integrity. We offer a variety of standard connector types, including FC, SC, ST, LC, etc., to accommodate different applications, as well as hybrid and specialized adapters to meet specific application needs.

Features

- 1. 100% inspected prior to shipment
- 2. Materials compliant to RoHS
- 3. Meet IEC, Telcordia-GR-326 and JIS performance requirement.
- 4. High precision alignment sleeve

Application

- 1. CATV System
- 2. Telecommunications
- 3. Optical Networks
- 4. Testing/Measurement Instruments
- 5. Fiber To the Home
- 6. Feature: High size precision; Good repeatability; Good changeability; Good temperature stabilization. High wearable.

Mechanical Specifications

Operating Temperature	-40 to +75° C
Storage Temperature	-40 to +85º C
Temperature Cycling	-40 to +75° C, 40 cycles=0.2dB change
High Temperature	70°c for 96Hrs, <0.4dB change
Damp Heat	40° C at 93%RH for 96 Hrs, <0.4dB change
Vibration-Mated Pair	10-55Hz, 1.5mm P to P <0.2dB change
Mating Durability	500 Mating Cycles, clean every 25, <0.2dB change





Q1: What is the warranty of FiberMania's fiber patch cord?

A: FiberMania warrants that all fiber patch cords supplied are free from defects in material and workmanship for a period of five (5) years from the date of supply. All fiber optic bulk cables are UL profiled and every single cable is 100% tested.

Q2: Is it possible to customize our brand information on your fiber cable?

A: Yes, we can print your brand name onto our cable jacket and 1KM total cable length is requested.

Q3: Can you do 3D interferometer test?

A: Yes, we do the 3D test per our customer's request, we can have the pass rate over 90% and even 100% if necessary.

Q4: What is your MOQ of your products?

A: We only have MOQ for some special customized cable order, we request 1km as the total length of the bulk cable, you may consider stock the bulk cable with us for your urgent order production.

Q5: Are free samples available from you?

A: Yes, we are always happy to offer the free samples for all of our customers' projects provided that the total cost is under 50 US dollars.

Q6: Do you accept OEM and ODM orders?

A: Absolutely yes, we have been doing OEM services since we start in this business, and for every single label, printing, bag and carton design, we always treat it seriously and do it nicely. Our engineers can help you with your current design and even can open the new tooling for your specific project.





17704025189



sales@fiber-mania.com



optical-fibercables.com

3F, Building A2, Yinlong Industrial Park, Longdong, Longgang District, Shenzhen, China, 518116