

6 Port LC Fiber Patch Panel Loaded W/6 LC Fiber Adapter Panel

Basic Information

Place of Origin: Shenzhen, China
Brand Name: FIBERMANIA
Certification: ISO, UL, CE, RoHS
Model Number: FAP-LCAD6LS
Minimum Order Quantity: 10 Pieces
Price: Negotiable
Packaging Details: Polybag

Delivery Time: 7-10 working days
 Payment Terms: T/T, Western Union, L/C
 Supply Ability: 100000PCS/Month



Product Specification

Name: Fiber Optic Patch Panel 6 Port

• Number Of Ports: 6

Adapter Type: LC Duplex
Fiber Count: 12 Fibers
Dimensions (HxW): 129x29mm

• Durability: ≤500 Mating Cycles

Material Of Plate: Steel, Powder-coated Black

• Application: LGX Patch Panel

Color: Green/Blue/Beige/Aqua/Magenta

• Highlight: 6 Port LC Fiber Patch Panel,

W/6 LC Fiber Adapter Panel, Fiber Optic Patch Panel 6 Port



More Images







Product Description

LC Adapter Panel 6 Ports Loaded w/6 LC Duplex Single Mode or Multimode Adapter

The adapter panel is a versatile device designed to connect and convert various types of interfaces, commonly found in electronic devices and computer systems. Its primary function is to ensure compatibility among devices of different standards or types, enabling seamless transmission of data and signals. Our Adapter Plates are meticulously crafted to complement fiber optic wall mount enclosures and patch panels, showcasing their robustness for field installations. Each Fiber Adapter Panel exemplifies a high standard of professionalism tailored for specific application sites, offering the added convenience of easy integration into fiber cabinets. This design simplifies the process and facilitates a user-friendly plug-and-play experience.

Features

- 1. Tool-less snap installation for easier moves, adds, and changes
- 2. High precision to ensure maximum connection between cables
- 3. Fast and easy installation for fiber optic patch panel
- 4. Available in grey and black colors
- 5. Available in white and black buckle
- 6. LGX design

Application

- 1. Datacenter
- 2. Network installations

Mechanical Specifications

Operating Temperature	-40 to +75° C
Storage Temperature	-40 to +85º C
Temperature Cycling	-40 to +75° C, 40 cycles=0.2dB change
High Temperature	70°c for 96Hrs, <0.4dB change
Damp Heat	40° C at 93%RH for 96 Hrs, <0.4dB change
Vibration-Mated Pair	10-55Hz, 1.5mm P to P <0.2dB change
Mating Durability	500 Mating Cycles, clean every 25, <0.2dB change





Q1: What is the warranty of FiberMania's fiber patch cord?

A: FiberMania warrants that all fiber patch cords supplied are free from defects in material and workmanship for a period of five (5) years from the date of supply. All fiber optic bulk cables are UL profiled and every single cable is 100% tested.

Q2: Is it possible to customize our brand information on your fiber cable?

A: Yes, we can print your brand name onto our cable jacket and 1KM total cable length is requested.

Q3: Can you do 3D interferometer test?

A: Yes, we do the 3D test per our customer's request, we can have the pass rate over 90% and even 100% if necessary.

Q4: What is your MOQ of your products?

A: We only have MOQ for some special customized cable order, we request 1km as the total length of the bulk cable, you may consider stock the bulk cable with us for your urgent order production.

Q5: Are free samples available from you?

A: Yes, we are always happy to offer the free samples for all of our customers' projects provided that the total cost is under 50 US dollars.

Q6: Do you accept OEM and ODM orders?

A: Absolutely yes, we have been doing OEM services since we start in this business, and for every single label, printing, bag and carton design, we always treat it seriously and do it nicely. Our engineers can help you with your current design and even can open the new tooling for your specific project.





17704025189



sales@fiber-mania.com



optical-fibercables.com

3F, Building A2, Yinlong Industrial Park, Longdong, Longgang District, Shenzhen, China, 518116