

Fiber Optic Patch Panel 8 Port Loaded W/8 SC Single Mode Or Multimode Adapter

Our Product Introduction

for more products please visit us on optical-fibercables.com

Basic Information

- Place of Origin: Shenzhen, China
- Brand Name: FIBERMANIA
- Certification: ISO, UL, CE, RoHS
- Model Number: FAP-SC8LS
- Minimum Order Quantity: 10 Pieces
- Price: Negotiable
- Packaging Details: Polybag
- Delivery Time: 7-10 working days
- Payment Terms: T/T, Western Union, L/C
- Supply Ability: 100000PCS/Month



Product Specification

- Number Of Ports: 8
- Fiber Count: 8 Fibers
- Adapter Type: SC Simplex
- Fiber Mode: Single Mode Or Multimode
- Material Of Plate: Steel, Powder-coated Black
- Dimensions (HxW): 129x29mm
- Application: LGX Patch Panel
- Color: Green/Blue/Beige/Aqua/Magenta
- Highlight: **Fiber Optic Patch Panel 8 Port,
Multimode Fiber Optic Patch Panel,
Single Mode Patch Panel 8 Port**



More Images



Product Description

SC Adapter Panel 8 Ports Loaded w/8 SC Single Mode or Multimode Adapter

An SC 8-port LGX adapter plate featuring six green SC duplex adapters. This fiber optic adapter patch panel plate is compatible with most common fiber optic patch panels and wall mounts. FiberMania utilizes this type of adapter plate in many of our wall mounts and patch panels. LGX stands for Light Guide Cross-Connect. Our LGX adapter plates adhere to standard dimensions and center pin spacing, ensuring a seamless fit across all patch panels. This standardized design allows for easy integration with any LGX-compatible system. Furthermore, LGX adapter plates support all standard fiber optic connector types, enhancing their versatility and usability.

Features

1. LGX footprint with our standard 11.80cm (4.646") pin spacing
2. Dimensions: 13.03cm (5.130") x 2.92cm (1.150")
3. All metal construction
4. Black powder coated (inflammable)
5. The LGX adapter plate is interchangeable allowing for use in a wide range of products
6. Installation is made easy with Push/Pull Pins
7. Connectors are screwed in to prevent rattling
8. RoHS compliant

Application

1. Datacenter
2. Network installations

Mechanical Specifications

Operating Temperature	-40 to +75° C
Storage Temperature	-40 to +85° C
Temperature Cycling	-40 to +75° C, 40 cycles=0.2dB change
High Temperature	70°c for 96Hrs, <0.4dB change
Damp Heat	40° C at 93%RH for 96 Hrs, <0.4dB change
Vibration-Mated Pair	10-55Hz, 1.5mm P to P <0.2dB change
Mating Durability	500 Mating Cycles, clean every 25, <0.2dB change





FAQ

Q1: What is the warranty of FiberMania's fiber patch cord?

A: FiberMania warrants that all fiber patch cords supplied are free from defects in material and workmanship for a period of five (5) years from the date of supply. All fiber optic bulk cables are UL profiled and every single cable is 100% tested.

Q2: Is it possible to customize our brand information on your fiber cable?

A: Yes, we can print your brand name onto our cable jacket and 1KM total cable length is requested.

Q3: Can you do 3D interferometer test?

A: Yes, we do the 3D test per our customer's request, we can have the pass rate over 90% and even 100% if necessary.

Q4: What is your MOQ of your products?

A: We only have MOQ for some special customized cable order, we request 1km as the total length of the bulk cable, you may consider stock the bulk cable with us for your urgent order production.

Q5: Are free samples available from you?

A: Yes, we are always happy to offer the free samples for all of our customers' projects provided that the total cost is under 50 US dollars.

Q6: Do you accept OEM and ODM orders?

A: Absolutely yes, we have been doing OEM services since we start in this business, and for every single label, printing, bag and carton design, we always treat it seriously and do it nicely. Our engineers can help you with your current design and even can open the new tooling for your specific project.



☎ 17704025189

✉ sales@fiber-mania.com

🌐 optical-fibercables.com

3F, Building A2, Yinlong Industrial Park, Longdong, Longgang District, Shenzhen, China, 518116