



## 6 Port Fiber Optic Adapter Panels Loaded W/6 ST Single Mode Or Multimode Adapter

Our Product Introduction

for more products please visit us on [optical-fibercables.com](http://optical-fibercables.com)

### Basic Information

- Place of Origin: Shenzhen, China
- Brand Name: FIBERMANIA
- Certification: ISO, UL, CE, RoHS
- Model Number: FAP-ST6LS
- Minimum Order Quantity: 10 Pieces
- Price: Negotiable
- Packaging Details: Polybag
- Delivery Time: 7-10 working days
- Payment Terms: T/T, Western Union, L/C
- Supply Ability: 100000PCS/Month



### Product Specification

- Number Of Ports: 6
- Material Of Adapter: Nickel-plated Copper
- Material Of Sleeve: Zirconia Ceramic
- Adapter Color: Plated
- Adapter Type: ST Simplex
- Fiber Mode: Single Mode Or Multimode
- Dimensions (HxW): 129x29mm
- Application: LGX Patch Panel
- Highlight: **6 Port Fiber Optic Adapter Panels, Single Mode Fiber Optic Adapter Panels, 6 Port Fiber Optical Patch Panel**



### More Images



## Product Description

### ST Adapter Panel 6 Ports Loaded W/6 ST Single Mode Or Multimode Adapter

The LGX ST series adapter panel comes pre-loaded with fiber adapters, offering a reliable means to connect backbone-to-backbone or backbone-to-horizontal fiber cabling. When used with LGX series enclosures and splice trays for fusion splicing applications or pre-terminated Plug-and-Play cabling systems, it provides a more stable and compact solution for your network.

The LGX High Density Series is a versatile option available in multiple sizes (1U, 2U, and 4U) and styles, making it ideal for building backbones, data centers, and enterprise applications.

#### Features

1. Visible port identification helps to follow array connection
2. LGX design
3. Fast and easy installation for fiber optic patch panel
4. Available in grey and black colors
5. Available in white and black buckle

#### Application

1. Datacenter
2. Network installations

#### Mechanical Specifications

Operating Temperature	-40 to +75° C
Storage Temperature	-40 to +85° C
Temperature Cycling	-40 to +75° C, 40 cycles=0.2dB change
High Temperature	70°c for 96Hrs, <0.4dB change
Damp Heat	40° C at 93%RH for 96 Hrs, <0.4dB change
Vibration-Mated Pair	10-55Hz, 1.5mm P to P <0.2dB change
Mating Durability	500 Mating Cycles, clean every 25, <0.2dB change





#### FAQ

Q1: What is the warranty of FiberMania's fiber patch cord?

A: FiberMania warrants that all fiber patch cords supplied are free from defects in material and workmanship for a period of five (5) years from the date of supply. All fiber optic bulk cables are UL profiled and every single cable is 100% tested.

Q2: Is it possible to customize our brand information on your fiber cable?

A: Yes, we can print your brand name onto our cable jacket and 1KM total cable length is requested.

Q3: Can you do 3D interferometer test?

A: Yes, we do the 3D test per our customer's request, we can have the pass rate over 90% and even 100% if necessary.

Q4: What is your MOQ of your products?

A: We only have MOQ for some special customized cable order, we request 1km as the total length of the bulk cable, you may consider stock the bulk cable with us for your urgent order production.

Q5: Are free samples available from you?

A: Yes, we are always happy to offer the free samples for all of our customers' projects provided that the total cost is under 50 US dollars.

Q6: Do you accept OEM and ODM orders?

A: Absolutely yes, we have been doing OEM services since we start in this business, and for every single label, printing, bag and carton design, we always treat it seriously and do it nicely. Our engineers can help you with your current design and even can open the new tooling for your specific project.

 **FIBERMANIA** Shenzhen FiberMania Technology Co., Ltd.

 17704025189

 [sales@fiber-mania.com](mailto:sales@fiber-mania.com)

 [optical-fibercables.com](http://optical-fibercables.com)

3F, Building A2, Yinlong Industrial Park, Longdong, Longgang District, Shenzhen, China, 518116