



FIBERMANIA

Shenzhen FiberMania Technology Co., Ltd.
optical-fibercables.com

MTP/MPO Multimode Simplex Adapter With SC Footprint Aqua

Our Product Introduction

Basic Information

- Place of Origin: Shenzhen, China
- Brand Name: FiberMania
- Certification: ISO, UL, CE, RoHS
- Model Number: MPOAQP
- Minimum Order Quantity: 10 Pieces
- Price: Negotiable
- Packaging Details: PE bag or OEM service optional
- Delivery Time: 5 days
- Payment Terms: T/T, Western Union, L/C
- Supply Ability: 10000 Pieces per day



Product Specification

- Transmission Medium: Multimode
- Number Of Cores: Single-Core
- Multimode Adaptor: US Conec MTP/MPO
- Keyway: Opposed (up-Down)
- Adapter Port: Single
- Footprint: SC
- Durability: 1000 Times
- Insertion Loss: $\leq 0.35\text{dB}$
- Color: Aqua
- Highlight: **Multimode MTP MPO Adapter ,
Simplex MTP MPO Adapter ,
Aqua MTP MPO Adapter**

for more products please visit us on optical-fibercables.com

Product Description

MTP/MPO Multimode Simplex Adapter With SC Footprint Aqua

MTP/MPO fiber optic adapter enable quick and easy connections of single-mode and multimode fibers. Fiber optic adapters are used to provide a cable to cable or cable to equipment fiber optic connection. There are many kinds of fiber optic adapters, including MTP/MPO, FC, SC, LC, MU, ST, and MTRJ. With its simple to use locking thread mechanism preventing accidental disconnection, this provides a very secure connection. This type of adapter meets appropriate standards and is perfect for your parallel optics and MTP adapter needs.

Features

1. Compact design, accomodating 4,8 or 12 fiber ribbons
2. High precision alignment
3. Low insertion and return loss and back reflection

Applications

1. Data center
2. Telecommunication networks
3. Premise installations
4. LAN and WAN
5. FTTX
6. Broadband network



Specifications

Parameter	SC/FC/LC/ST/MPO/DIN/Hybrid				
	Unit	SM			MM
		PC	UPC	APC	PC
Insertion Loss	dB	≤0.35	≤0.35	≤0.35	≤0.35
Return Loss	dB	≥45	≥50	≥60	≥30
Exchangeability	dB	≤0.2			
Repeatability	dB	≤0.1			
Durability	Times	≥1000			
Operating Temperature	°C	-20~75			
Storage Temperature	°C	-20~85			



FIBERMANIA Shenzhen FiberMania Technology Co., Ltd.



17704025189



sales@fiber-mania.com



optical-fibercables.com

3F, Building A2, Yinlong Industrial Park, Longdong, Longgang District, Shenzhen, China, 518116