

19" 2U CAT.5E UTP Unshielded 48 Port Copper Patch Panel With Label Mark, Dual IDC, Black

Basic Information

Place of Origin: Shenzhen, China
Brand Name: FIBERMANIA
Certification: CE, RoHS
Model Number: PP-C5U48DBK
Minimum Order Quantity: 1 Piece

Price: Negotiable
Packaging Details: 1PC/Box

• Payment Terms: T/T, Western Union, L/C

• Supply Ability: 1000 Pieces



Product Specification

Category: CAT.5ENo. Of Ports: 48No. Of Rack Spaces: 2U

• Shielding Type: Unshielded

Material: SPCC + ABS Plastics

• Housing: 1.5mm SPCC

• Color: Black

• Wiring Scheme: T568A/T568B

• Type Of Patch Panel: Flat

Approvals: RoHS Compliant

Highlight: Unshielded Copper Patch Panel,

48 Port Copper Patch Panel, 19" Copper Patch Panel

Product Description

19" 2U CAT.5E UTP Unshielded Patch Panel, 48 Ports, With Label Mark, Dual IDC, Black

19" 2U CAT.5E UTP Unshielded Patch Panel, 48 Ports, With Label Mark, Dual IDC, Black is a type of network equipment commonly used in structured cabling systems. It is a patch panel that uses unshielded cables, meaning there is no extra protective layer around the individual wires. It has 48 individual ports, allowing for the connection of up to 48 different cables. In summary, this product is a 48-port, 19-inch rack-mounted patch panel used for connecting CAT5e network cables, typically in a server room or data center. It is designed to fit into a standard 19-inch rack and comes with labeling for easier identification of connections.

Features

- 1. Capacity: 48 Ports (2U)
- 2. Material: 1.5mm SPCC
- 3. Cabinet designed, label and inlaid marks for convenience of identification and network management
- 4. Accessories include cable ties & mounting screws
- 5. With fixed cable manager
- 6. RoHS compliant

Application

- 1. Gigabit Ethernet
- 2. LAN aggregation
- 3. Data center management
- 4. Equipment rooms
- 5. Wiring closets



Specifications

<u> </u>	
Product	Cat3/Cat5e/Cat6/Cat6a Copper Patch Panel
Port Number	8, 12, 18, 24, 36, 48, 96port
Front Panel	Cold rolled steel
Plastic	High impact and flame retardant plastic,UL94V-0 rated
IDC Accept	22-26 AWG Solid Wire
Transmission Standards	ANSI/TIA-568.2-D ISO/IEC 11801 Class E
Wiring	T568A T568B
Insulation Resistance	Min.500 Mega Ohms
Contact Resistance	Max.20milli-Ohms
Dielectric Strength	750V AC RMS 60Hz 1min
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Flammability Rating	UL 94 V-0

Q1: What is the warranty of FiberMania's fiber patch cord?

A: FiberMania warrants that all fiber patch cords supplied are free from defects in material and workmanship for a period of five (5) years from the date of supply. All fiber optic bulk cables are UL profiled and every single cable is 100% tested.

Q2: Is it possible to customize our brand information on your fiber cable?

A: Yes, we can print your brand name onto our cable jacket and 1KM total cable length is requested.

Q3: Can you do 3D interferometer test?

A: Yes, we do the 3D test per our customer's request, we can have the pass rate over 90% and even 100% if necessary.

Q4: What is your MOQ of your products?

A: We only have MOQ for some special customized cable order, we request 1km as the total length of the bulk cable, you may consider stock the

bulk cable with us for your urgent order production.

Q5: Are free samples available from you?

A: Yes, we are always happy to offer the free samples for all of our customers' projects provided that the total cost is under 50 US dollars.

Q6: Do you accept OEM and ODM orders?

A: Absolutely yes, we have been doing OEM services since we start in this business, and for every single label, printing, bag and carton design, we always treat it seriously and do it nicely. Our engineers can help you with your current design and even can open the new tooling for your specific project.

FIBERMANIA Shenzhen FiberMania Technology Co., Ltd.

17704025189

sales@fiber-mania.com

optical-fibercables.com

3F, Building A2, Yinlong Industrial Park, Longdong, Longgang District, Shenzhen, China, 518116