

High Density MTP to LC Module Cassette with 6 LC Ports and Zirconia Ceramic Sleeves for 40 and 100Gbps Protocols

Basic Information

Certification: CE, ISO, RoHS

Minimum Order Quantity: 10Price: 14.5



Product Specification

Fiber Count: 12 Fibers

Fiber Mode: OM1 62.5/125µmFront Connector: LC UPC Quad

Rear Connector: US Conec MTP® UPC (Pinned)

LC Ports: 6 PortsMTP Ports: 1 Port

MTP Adapter: Key Up To Key Down

Housing Type: Cassette

Sleeve Material: Zirconia CeramicCassette Material: Aluminium (AL5052)

Polarity: Type A
Operating Temperature: -25°C~+70°C
Storage Temperature: -25°C~+70°C
Relative Humidity: ≤85%(+30°C)

Dimensions: 129mm X 155mm X 29mm



More Images









High Density MTP 12 (Male) to 6 x LC Duplex Module Cassette Fully Loaded

MPO/MTP cassette capable of accepting 6-24 fibers. These cassettes are suitable for use with Singlemode, Multimode 62.5 and 50um, as well as Laser Optimized, OM3 applications and are available in LC, SC, ST, FC, MTRJ connector types. MPO/MTP cassette comes preinstalled with the required adapters featuring Zirconia Ceramic sleeves for enhanced compatibility with all applications. Adapters are color-coded according to the application in use (Blue = 9/125; Beige = 62.5 and 50um; Aqua = OM3; Green = APC). All adapters come standard with dust covers.

Key Features

High density - can be applied with 12 fibers and 24 fibers

Ideal for Data Center Applications

MTP/MPO standard compliant multi-fiber connector

Available with OS1/2, OM1, OM2, OM3, OM4 fiber grades

Available with different fiber adapter ports, SC, LC, ST, FC etc.

Rapid deployment terminated modular system saves installation time and labor

Applications

LAN, WAN and SAN

Data center

Telecommunication networks

Parallel Optics

Emerging 40 and 100Gbps Protocols

Mechanical Characteristics

| Parameter | Value |
|-----------------------|----------------------|
| Operating temperature | -25°C~+70°C |
| Storage temperature | -25°C~+70°C |
| Relative humidity | ≤85%(+30°C) |
| Color | Black |
| Max. Capacity | 12 port/24 port (LC) |
| Dimension(WxHxD) | 129mm x 155mm x 29mm |

Environmental Properties

| Connector | Cable | Performance Level | |
|------------------|---------------------|-------------------|---------|
| | | Standard | Elite |
| MPO/MTP | OM1/OM2/OM3/OM4/OM5 | ≤0.70dB | ≤0.35dB |
| | LC/SC/FC/ST | ≤0.20dB | ≤0.10dB |
| Return Loss (RL) | | ≥20dB | ≥30dB |

Quality Testing Program

IL and RL Testing

Conduct testing on the insertion loss and return loss of cables to verify their reach and ensure stable signal transmission.

3D Interferometer Testing

Evaluate the connectors or ferrules of cables to verify that the apex offset, radius of curvature, and fiber height are within the specified parameters, ensuring a successful connection of fiber optic lines.

End-Face Inspection Examine the connector end face for any scratches, defects, or contamination to ensure the tips remain clean. This practice enhances communication quality and reliability, thereby contributing to network uptime. **Production Equipment** Packaging & Shipping **Frequently Asked Questions** Q1: What is the warranty of FiberMania's fiber patch cord? A: FiberMania warrants that all fiber patch cords supplied are free from defects in material and workmanship for a period of five (5) years from the date of supply. All fiber optic bulk cables are UL profiled and every single cable is 100% tested. Q2: Is it possible to customize our brand information on your fiber cable? A: Yes, we can print your brand name onto our cable jacket and 1KM total cable length is requested. Q3: Can you do 3D interferometer test? A: Yes, we do the 3D test per our customer's request, we can have the pass rate over 90% and even 100% if necessary. Q4: What is your MOQ of your products? A: We only have MOQ for some special customized cable order, we request 1km as the total length of the bulk cable, you may consider stock the bulk cable with us for your urgent order production. Q5: Are free samples available from you? A: Yes, we are always happy to offer the free samples for all of our customers' projects provided that the total cost is under 50 US dollars.





sales@fiber-mania.com

poptical-fibercables.com

3F, Building A2, Yinlong Industrial Park, Longdong, Longgang District, Shenzhen, China, 518116